



DF9 is a crack-bridging composite sealant used under tiles in interior areas. DF9 is tested according to EN 14891.

PROPERTIES

- Highly elastic
- Open to vapour diffusion
- Solvent-free
- Can be rolled up and trowelled

AREAS OF APPLICATION

Sealing of

- concrete, lightweight concrete, and porous concrete
- joint full brickwork
- cement screeds and calcium sulphate screeds
- plasters of the mortar categories CS II, CS III and CS IV in accordance with EN 998 (compressive strength $\geq 1.5 \text{ N/mm}^2$) and gypsum plasters according to EN 13279 (compressive strength $\geq 2.0 \text{ N/mm}^2$)
- Botament BP building boards
- fibre cement boards
- gypsum plaster boards
- gypsum walls
- mastic asphalt screeds (IC 10)

SUBSTRATE PREPARATION

The substrate must be in the following condition:

- dry, clean and frost-free
- stable
- free from grease, paint, cement laitance, separating agents and loose particles

Please also note:

- existing cracks must be closed professionally
- level irregular substrates
- on surfaces full of pores or blowholes a scratch coat (e.g. made of M21 Classic or MULTISTAR) has to be applied first
- absorbent substrates must be primed with D11 or D1 Speed
- apply a thin contact layer made of DF9 on existing tile coverings

APPLICATION

- stir DF9 thoroughly and apply it with a sheepskin roller or a trowel in at least two layers (the previous layer of DF9 must have dried out completely)

The minimum dry layer thickness of the sealing must reach 0.5 mm (correlating with a wet layer thickness of 0.8 mm). The maximum dry layer thickness must not exceed 1 mm.

The subsequent tile fitting can be performed using M21 Classic, MULTISTAR, M12 Stone, M20 or M20 S1.

Joints, internal and external corners as well as penetrations are covered by including SB78 system sealing tape or SB20 system sealing tape and accessories or SB100 stretcable zone sleeve in the first layer of the sealant material and worked over with the second layer.

The connection of the sealant made of DF9 to bath and shower tubs is done by using SB78 WB tub sealing tape.

IMPORTANT ADVISORIES

During the hardening process DF9 has to be protected from moisture, draughts, solar radiation as well as from as from strong temperature fluctuations. While curing the relative humidity must not exceed 80 %.

DF9 must not be exposed to mechanical loads.

Avoid moisture on the rear-side. DF9 is not suitable for the use in areas being wet permanently and for sealings against negative water pressure as well as against additional chemical exposure.

You can view or download the safety datasheet at www.botament.com.

To achieve optimal results we recommend conducting a site-specific test sample prior to using.

TECHNICAL VALUES & PRODUCT CHARACTERISTICS

Characteristic	Unit	Value	Comments
Density	kg/dm ³	~ 1.45	
Consumption	kg/m ²	~ 1.2	for manufacturing the necessary dry layer thickness of 0.5 mm
Interval	hours	~ 1.5 - 2	between the individual coatings
		~ 3 - 5	between the final coat and the application of the tile covering
Application conditions	°C	> 8 < 30	
All technical values are laboratory results determined at 21°C ±2°C and 50% relative humidity.			
base	plastic dispersion		
delivery form	for rolling up		
	5 kg (grey)		
	12 kg (grey)		
	21 kg (grey + light grey)		
	for trowelling		
	12 kg (grey)		
	21 kg (grey + light grey)		
Storage	Can be stored in cool and dry conditions for at least 12 months in original unopened packs. Protect from frost.		
Cleaning agent	when fresh: water, when dry through: mechanical		

Note: The information contained in this data sheet is based on our experience and is correct to the best of our knowledge. It is, however, not binding. It will need to be adapted to the requirements of the individual structure, to the specific application and to non-standard local conditions. Application-specific conditions must be checked in advance by the planning engineer/specifier and, where different from the standard conditions indicated, will require individual approval. Technical advice provided by MC's specialist consultants does not replace the need for a planning review by the client or its agents in respect of the history of the building or structure. Subject to this prerequisite, we are liable for the correctness of this information within the framework of our terms and conditions of sale and delivery. Recommendations of our employees deviating from the information given in our data sheets are only binding for us if they are confirmed in writing. In all cases, the generally accepted rules and practices reflecting the current state of the art must be observed. The information given in this technical data sheet is valid for the product supplied by the country company listed in the footer. It should be noted that data in other countries may differ. The product data sheets valid for the relevant foreign country must be observed. The latest technical data sheet shall apply to the exclusion of previous, duly superseded versions; the date of issue in the footer must be observed. The latest version is available from us on request or may be downloaded from our website. [2300011961]

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· **1.1 Product identifier**

· **Trade name** DF 9 (R)

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**

No further relevant information available.

· **Application of the substance / the mixture**

Sealant

· **1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:** BOTAMENT Systembaustoffe
Am Kruppwald 1
D-46238 Bottrop

Tel.: ++49(0)2041 101-90
Fax.: ++49(0)2041 101-988

· **Informing department:**

Product safety department.
msds@botament.com

· **1.4 Emergency telephone number:**

Tel.: +49 / (0)700 24112112 (MCR)
Tel.: +48612864565

SECTION 2: Hazards identification

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**

Skin Sens. 1 H317 May cause an allergic skin reaction.

· **2.2 Label elements**

· **Labelling according to**

Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation.

· **Hazard pictograms**



GHS07

· **Signal word**

Warning

· **Hazard-determining**

components of labelling:

2-methyl-2H-isothiazol-3-one
2-octyl-2H-isothiazol-3-one
1,2-benzisothiazol-3(2H)-one

· **Hazard statements**

H317 May cause an allergic skin reaction.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P103 Read carefully and follow all instructions.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P280 Wear protective gloves.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 1)

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P321 Specific treatment (see on this label).

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Additional information:** Contains biocidal products: 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one, 2-octyl-2H-isothiazol-3-one

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· **3.2 Mixtures**

· **Description:** Mixture consisting of the following components.

· **Dangerous components:**

CAS: 14808-60-7	crystalline silica STOT RE 1, H372	<5%
CAS: 13463-67-7 EINECS: 236-675-5	titanium dioxide Carc. 2, H351	<1%
CAS: 1336-21-6 EINECS: 215-647-6	ammonia Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; STOT SE 3, H335 Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	<0.25%
CAS: 2634-33-5 EINECS: 220-120-9	1,2-benzisothiazol-3(2H)-one Eye Dam. 1, H318; Aquatic Acute 1, H400; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 %	<0.05%

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 2)

CAS: 2682-20-4 EINECS: 220-239-6	2-methyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1); Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C \geq 0.0015 %	\geq 0.0015-<0.025%
CAS: 26530-20-1 EINECS: 247-761-7	2-octyl-2H-isothiazol-3-one Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 ATE: LD50 oral: 125 mg/kg LD50 dermal: 311 mg/kg LC50/4 h inhalative: 0.27 mg/l Specific concentration limit: Skin Sens. 1A; H317: C \geq 0.0015 %	\geq 0.00025-<0.0015%

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information** No special measures required.
- **After inhalation** Void
- **After skin contact** The product is not skin irritating.
- **After eye contact** Rinse opened eye for several minutes under running water.
- **After swallowing** Rinse out mouth and then drink plenty of water.
In case of persistent symptoms consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents** Void
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** No special measures required.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures** *Not required.*
- **6.2 Environmental precautions:** *No special measures required.*
- **6.3 Methods and material for containment and cleaning up:** *Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).*
- **6.4 Reference to other sections** *No dangerous materials are released.*

* **SECTION 7: Handling and storage**

- **7.1 Precautions for safe handling** *No special measures required.*
- **Information about protection against explosions and fires:** *No special measures required.*
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and containers:** *No special requirements.*
- **Information about storage in one common storage facility:** *Not required.*
- **Further information about storage conditions:** *None.*
- **Storage class** *12*
- **7.3 Specific end use(s)** *No further relevant information available.*

* **SECTION 8: Exposure controls/personal protection**

- **8.1 Control parameters**
- **Components with critical values that require monitoring at the workplace:** *The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.*
- **Additional information:** *The lists that were valid during the compilation were used as basis.*
- **8.2 Exposure controls**
- **Appropriate engineering controls** *No further data; see section 7.*
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures** *The usual precautionary measures should be adhered to in handling the chemicals.*
- **Breathing equipment:** *Not required.*
- **Hand protection** *Not required.*

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 4)

- **Material of gloves** -
- **Penetration time of glove material** -
- **Eye/face protection** Safety glasses

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

- **Colour:** Grey
- **Smell:** Characteristic
- **Melting point/freezing point:** Not determined
- **Boiling point or initial boiling point and boiling range** 100 °C (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
- **Flash point:** Not applicable
- **pH at 20 °C** 7-8
- **Viscosity:**
- **Kinematic viscosity** Not determined.
- **dynamic at 20 °C:** 40000 mPas
- **Solubility**
- **Water:** Soluble
- **Steam pressure at 20 °C:** 23 hPa (CAS: 7732-18-5 water, distilled, conductivity or of similar purity)
- **Density and/or relative density**
- **Density at 20 °C** 1.53 g/cm³

· **9.2 Other information**

- **Appearance:**
- **Form:** Pasty
- **Important information on protection of health and environment, and on safety.**
- **Self-inflammability:** Product is not selfigniting.
- **Explosive properties:** Product is not explosive.

· **Information with regard to physical hazard classes**

- **Explosives** Void
- **Flammable gases** Void
- **Aerosols** Void
- **Oxidising gases** Void
- **Gases under pressure** Void
- **Flammable liquids** Void
- **Flammable solids** Void
- **Self-reactive substances and mixtures** Void
- **Pyrophoric liquids** Void
- **Pyrophoric solids** Void
- **Self-heating substances and mixtures** Void
- **Substances and mixtures, which emit flammable gases in contact with water** Void

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 5)

· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values that are relevant for classification:**

CAS: 13463-67-7 titanium dioxide

Oral	LD50	>10000 mg/kg (rat)
Dermal	LD50	>10000 mg/kg (rabbit)
Inhalative	LC50/4 h	>6.8 mg/l (rat)

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

Oral	LD50	1020 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

Oral	LD50	50-300 mg/kg (rat)
Inhalative	LC50/4 h	0.11 mg/l (rat)

CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one

Oral	LD50	125 mg/kg (ATE) 500 mg/kg (rat)
Dermal	LD50	311 mg/kg (ATE) >2000 mg/kg (rat)
Inhalative	LC50/4 h	0.27 mg/l (ATE) 0.6 mg/l (rat)

- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 6)

- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one

EC50/72h 0.067 mg/l (Pseudokirchneriella subcapitata)

0.11 mg/l (Selenastrum capricornutum)

LC50/96h 1.6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.1 mg/l (Daphnia magna)

CAS: 2682-20-4 2-methyl-2H-isothiazol-3-one

EC50/72h 0.157 mg/l (Pseudokirchneriella subcapitata)

LC50/96h 6 mg/l (Oncorhynchus mykiss)

EC50/48h 1.68 mg/l (Daphnies)

CAS: 26530-20-1 2-octyl-2H-isothiazol-3-one

EC50/48h 0.42 mg/l (Daphnien)

· **12.2 Persistence and degradability**

No further relevant information available.

· **12.3 Bioaccumulative potential**

No further relevant information available.

· **12.4 Mobility in soil**

No further relevant information available.

· **12.5 Results of PBT and vPvB assessment**

· **PBT:**

Not applicable.

· **vPvB:**

Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Additional ecological information:**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

GB

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 7)

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation** *Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*

· **Uncleaned packagings:**

· **Recommendation:** *Empty contaminated packagings thoroughly. They can be recycled after thorough and proper cleaning.*

· **Recommended cleaning agent:**

Water, if necessary with cleaning agent.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, ADN, IMDG, IATA** *Void*

· **14.2 UN proper shipping name**

· **ADR, ADN, IMDG, IATA** *Void*

· **14.3 Transport hazard class(es)**

· **ADR, ADN, IMDG, IATA**

· **Class** *Void*

· **14.4 Packing group**

· **ADR, IMDG, IATA** *Void*

· **14.5 Environmental hazards:**

· **Marine pollutant:** *No*

· **14.6 Special precautions for user**

Not applicable.

· **14.7 Maritime transport in bulk according to IMO instruments**

Not applicable.

· **Transport/Additional information:**

Not dangerous according to the above specifications.

· **UN "Model Regulation":**

Void

SECTION 15: Regulatory information

· **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Poisons Act**

· **Regulated explosives precursors**

None of the ingredients is listed.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 8)

· Regulated poisons

None of the ingredients is listed.

· Reportable explosives precursors

None of the ingredients is listed.

· Reportable poisons

CAS: 1336-21-6 ammonia

10%

· 15.2 Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- EUH071 Corrosive to the respiratory tract.

· Department issuing data specification sheet:

Environment protection department.

· Abbreviations and acronyms:

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- ATE: Acute toxicity estimate values
- Acute Tox. 3: Acute toxicity – Category 3
- Acute Tox. 4: Acute toxicity – Category 4
- Acute Tox. 2: Acute toxicity – Category 2

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 05.01.2024

Version number 21 (replaces version 20)

Revision: 05.01.2024

Trade name DF 9 (R)

(Contd. of page 9)

Skin Corr. 1: Skin corrosion/irritation – Category 1
Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Skin Sens. 1: Skin sensitisation – Category 1
Skin Sens. 1A: Skin sensitisation – Category 1A
Carc. 2: Carcinogenicity – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

*** Data compared to the previous version altered.**

GB

**Gemeinschaft Emissionskontrollierte
Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.**

Association for the Control of Emissions from Products
for Flooring Installation, Adhesives and Building Materials



Awarding of licence for the use of EMICODE

Licence Number:	8163/15.01.10
For the product	Botament DF9 Dichtfolie
Of company	Botament GmbH
Due to application date	22.06.2017

With reference to the classification in accordance with the directives as stipulated in § 10 of the GEV trademark constitution

on behalf of the GEV for the above mentioned product as per § 5, section 4 of the GEV trademark constitution is awarded the licence for the use of the GEV trademark



This product meets with the guidelines for the criteria of use listed reverse.
The company is ordinary member of the GEV.

OM063 **20.06.2022**
valid until 20.06.2027

The Secretary General
Association for the Control of Emissions in Products
for Flooring Installation, Adhesives and Building Materials (GEV)
Völklinger Straße 4 · D-40219 Düsseldorf

Requirement guidelines for the awarding of the EMICODE licence

The product mentioned on the front side of the licence has to fulfil among others the following criteria in accordance with the Constitution and the guidelines of the Technical Advisory Board of the GEV:

- The product meets all the legal requirements, especially the chemical laws and their specifications.
- The product is solvent free as specified in clause 2.4 of the “GEV Classification Criteria”, except if it is a surface treatment product. If the product is assigned to a GISCODE product group then this can be labelled.
- A safety data sheet (SDS) according to local law in its respectively valid version is issued for the product.
- Carcinogenic, mutagenic, reprotoxic substances of the categories 1A or 1B are not added during the manufacture of the product.
- The testing of the product is performed in accordance with the GEV Testing Method. VOC determination is performed in a test chamber followed by the Tenax / thermal desorption procedures with subsequent GC/MS analysis.
- The assignment of an EMICODE class is performed according to the following criteria and TVOC/TSVOC concentration levels. The corresponding EMICODE class shall be used to label the product:

1) Installation products, adhesives and construction products

Parameter	EC 1 ^{PLUS}	EC 1	EC 2
	max. allowed concentration [$\mu\text{g}/\text{m}^3$]		
TVOC after 3 days	≤ 750	≤ 1000	≤ 3000
TVOC after 28 days	≤ 60	≤ 100	≤ 300
TSVOC after 28 days	≤ 40	≤ 50	≤ 100
R value based on German AgBB LCI (NIK) after 28 days	1	-	-
Sum of non-assessable VOC	≤ 40	-	-
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Sum of form- and acetaldehyde	≤ 0.05 ppm	≤ 0.05 ppm	≤ 0.05 ppm
Sum of volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1

2) Products for floor surface treatments for parquet, mineral floors and resilient floorings

Parameter	EC 1 ^{PLUS}	EC 1	EC 2
	max. allowed concentration [$\mu\text{g}/\text{m}^3$]		
Sum TVOC + TSVOC after 28 days	≤ 100 thereof max. 40 SVOC	≤ 150 thereof max. 50 SVOC	≤ 450 thereof max. 100 SVOC
Formaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Acetaldehyde after 3 days	≤ 50	≤ 50	≤ 50
Any volatile C1A/C1B after 3 days	≤ 10	≤ 10	≤ 10
Any volatile C1A/C1B after 28 days	≤ 1	≤ 1	≤ 1