


TECHNICAL DATA SHEET

NATURAL STONE

PRODUCT IDENTIFICATION		
	Commercial Designation: Kandla Grey Indian Sandstone	
	Description: Stone suitable for exterior use in a variety of architectural situations	
	Petrographic Family: Sandstone	
	Origin: India	
	Application: External use for Path, Patios and Steps	
European Standards: (for outside specifications only)	EN1341: Slabs	CE
Technical Characteristics	Testing Standards	Declared Values
Dimensions	EN 12371; 2011	As per order.
Tolerance	EN 12371; 2011	+/-1.5mm
Packaging		Wooden crates/ wooden spacer/plastic wrapped
Surface Finish		Riven Surface
Edges		H cut edge
Sealing		
Resistance to Slipping	EN 14231; 2004	SRV dry 70 / SRV wet 68
Frost Resistance	EN12372 : 2006	After 12 cycles Flex strength: 22.7 MPa After 48 cycles Flex strength 21.00 MPa
Flexural Strength	EN12372 : 2006	23.7 MPa
Compressive Strength	EN1926 : 1999	380.3 kg/cm ²
Water Absorption	EN13755: 2001 EN1925: 1999	0.8% by weight 0.23% by capillary
Resistance to Wear	EN14157 : 2004	5.8 mm (average wear) 5.6 mm (individual wear)
Breaking Load (N)	IS13630	6.0 x 10 ³
Apparent Density	EN 1936 : 1999	2.70 %
Apparent Porosity	EN 1936 : 1999	0.45 %