



Bostik MSP107 Seal Bond

Multi-purpose Adhesive and Waterproofing Sealant

Date: 30 January 2018

Fact Sheet No.:

YOUR SMART ADVANTAGES

- Solvent and Isocyanate free with excellent adhesion on damp surfaces
- Excellent UV and weather resistance and non-corrosive to metals
- Can be painted and is compatible with most paints
- Retains original properties after compression or expansion

USES

Bostik MSP107 Seal Bond is a multi-purpose, multi-surface adhesive and waterproofing sealant with SM polymer technology. It is effective even on damp surfaces and is ideal for glass, zinc, wood, metal PVC.

It is an ideal solution for weatherproofing and is suitable for a wide range of materials and surfaces. Bostik MSP107 Seal bond has excellent UV and weather resistance and is non corrosive to metals. It can also be over painted after complete polymerisation

PRODUCT CHARACTERISTICS

| | |
|------------------|---|
| Colours | Black, Brown, Grey, white |
| Form | Paste |
| Elongation break | at >200% |
| Composition | SM Polymer |
| Product Code | 30606102 - Black 30606121 - Brown 30606110 - Grey 30606327 - White |

Storage/Shelf Life

18 months in original, unopened container. Store in a dry place at temperatures between +5°C and +30°C

TYPICAL PERFORMANCE DATA (Approx.)

Application Temperature

+5°C to +35°C

Service Temperature

-40°C to +100°C

Coverage

Calculated bead coverage in metres per 290ml cartridge:

- based on a joint size of 5mm in depth and 6mm in width: 9.60m
- based on a joint size of 8mm by 8 mm: 4.50m

Drying Times

- Skinning time approximately 20 minutes
- Tack-free time approximately 50 minutes
- Cure rate 3mm per 24 hours
- Uncured adhesive: remove with cleaning wipes or a cleaning solvent (Solvent AK).
- Dried adhesive: remove by scraping.

Solvent for Cleaning Up

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik MSP107 Seal Bond, refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/ireland

PREPARATION

1. Surfaces must be sound, clean and free from contaminants such as dust, oil, grease and any loose material.



FM 01696
BS EN ISO 9001:2008

Bostik Industries Ltd. Newtown, Swords, Co. Dublin, Ireland. Tel: +353 1 8624900 www.bostik.ie

2. Cut off the dome at the top of the cartridge taking care not to damage the thread. Cut the nozzle at a 45° angle to the required diameter and screw onto the cartridge.
3. Insert the cartridge into a cartridge gun and repeatedly squeeze the trigger until the adhesive appears.

APPLICATION

WATERPROOFING

Apply the sealant by extrusion, over a backing foam if necessary for deep joints (the joint depth should be no greater than 2/3 of the joint width).

Within 10 minutes of application, tool off the sealant with a spatula or tooling-knife rinsed in soapy water. Make sure the water does not seep between the joint wall and sealant in order to prevent loss of adhesion

ADHESION

Extrude the sealant in beads on one of the surfaces and join the substrates immediately, pressing down firmly to spread the adhesive. The bonding surfaces should not be handled or placed under stress for at least 24 hours

CLEANING

- Uncured adhesive: remove with cleaning wipes or a cleaning solvent
- Dried adhesive: remove by scraping

PRECAUTIONS IN USE

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/ireland for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik MSP107 Seal Bond is available at www.bostik.com/ireland.

BOSTIK HOTLINE

Smart help +353 1 8624998



FM 01696
BS EN ISO 9001:2008

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

| | | | |
|---|-----------------|-----------------|--|
| Sales | Tel: 01 8624999 | Fax: 01 8402186 | orders.bostik-irl@bostik.com |
| Technical Advice | Tel: 01 8624998 | Fax: 01 8402186 | |
| Technical Data & COSHH (MSDS) Data Sheets | Tel: 01 8624900 | Fax: 01 8402186 | |



FM 01696
BS EN ISO 9001:2008