



PRODUCT TECHNICAL CHARACTERISTICS

PRODUCT TYPE:	Dry pressed ceramic tile Eb > 10
GROUP:	BIII
USE:	Interior walls
MODEL:	SOLDEU
FORMAT:	7,5X30 cm
COLOR:	SERIE-TODOS COLORES-

<u>TRIAL</u>	<u>Normative</u>	<u>Requirements Minima</u>	<u>BESTILE</u>	
Dimensions	ISO10545-2	LENGTH±0.6% (max.±2.0mm)	300	
		WIDTH±0.6% (max.±2.0mm)	75	
		THICKNESS±0.5mm	10	
Water absorption	ISO10545-3	Eb >10%	12,62	
Breaking strength in N (Thickness ≥ 7.5mm)	ISO10545-4	600	869	
Modulus of rupture N/mm ²	ISO10545-4	12	20	
Frost resistance	ISO10545-12	PERFORM	PERFORM	
Thermal shock	ISO10545-9	PERFORM	PERFORM	
Chemical resistance:	ISO10545-13			
a) Acids		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
b) Alkalis		H	DECLARED VALUE	GHA
		L	DECLARED VALUE	GLA
c) Household products and salts for swimming		GB	GA	
Stains	ISO10545-14	3	5	

Date
11/05/2023

RESPONSIBLE
JUAN MANUEL GIMENO
FINISHED PRODUCT LABORATORY